



OPTIMA

ALUMINUM GOOSENECK TRAILERS

REDEFINED



Shown with triple axle and 60" double side door options.

Optima means the most of everything — style, strength and precision trailer building. Our motor-sports trailers feature standards never imagined. If you're looking for the best in aluminum trailers, Optima will be at the top of the list.



Nice profile! Optima goosenecks make a bold statement.



Standard, finished interior and exterior is completely fastenerless.



Flush, smooth transitions and even hardware are well designed.

STANDARD HIGHLIGHTS

- VHB fastenerless exterior and interior
- 96" rear ramp door w/spring assist, flap, heavy duty hinges and stainless latches
- Beavertail
- .050 exterior (white, black, red)
- 48" side door w/stepwell
- Electric brakes
- Extruded aluminum floor
- Enclosed riser area

- Insulated .030 aluminum interior walls and ceiling
- Wiring harness
- Pre-wired for 110v
- Stainless steel D-rings (4)
- Wire and framing for AC
- Non-powered roof vent
- Deluxe dome lights w/switch
- Cast aluminum front corners
- Seamless aluminum roof
- Bolted safety cables
- 6-year limited warranty

OPTION HIGHLIGHTS

- Hydraulic landing jack
- 60" double side door
- X Package
- Aluminum cabinets
- Generator and doors
- AC and heating options
- Awnings
- Observation deck
- 12v and 110v electrical
- Wheel and axle upgrades
- Aluminum wheels

	OPG8536TA5	OPG8540TA5	OPG8544TTA5	OPG8548TTA5	OPG8552TTA5
Overall length	35' 9"	39' 9"	43' 9"	47' 9"	51' 9"
Interior length	35' 4"	39' 4"	43' 4"	47' 4"	51' 4"
Interior width/BWW*	98"/83-1/2"	98"/83-1/2"	98"/83-1/2"	98"/83-1/2"	98"/83-1/2"
Interior height	6' 6-1/2"	6' 6-1/2"	6' 6-1/2"	6' 6-1/2"	6' 6-1/2"
Axles	7000 lb. tandem	7000 lb. tandem	7000 lb. triple	7000 lb. triple	7000 lb. triple
Ramp door opening	96"	96"	96"	96"	96"
Frame	4" I-beam	4" I-beam	4" I-beam	4" I-beam	4" I-beam
Tire size	LT235 85R16LRG	LT235 85R16LRG	LT235 85R16LRG	LT235 85R16LRG	LT235 85R16LRG
Curb weight	5500 lb.	5915 lb.	6330 lb.	6750 lb.	7170 lb.
GVWR	14,400 lb.	14,400 lb.	21,600 lb.	21,600 lb.	21,600 lb.
Payload capacity**	8900 lb.	8485 lb.	15,270 lb.	14,850 lb.	14,425 lb.
Exterior	.050 smooth	.050 smooth	.050 smooth	.050 smooth	.050 smooth

*Between wheel wells. **Optional equipment adds weight and lowers payload capacity.