

C u b 6 '



P O P U L A R O P T I O N S

ATP stoneguard

14" x 14" non-powered roof vent

12V dome light and switch

D-ring tie downs

32" or 36" side door

Ramp door

Light Package



T H E B E S T N A M E B E H I N D Y O U F O R T H E L O N G H A U L

Cub 6' Specifications

Model		CB6X10DS2	CB6X12DS2	CB6X14DS2	GC6X12DT2	GC6X14DT2	GC6X16DT2	GC6X18DT2
Overall	Length	14'	16'	18'	16'	18'	20'	22'
	Width	92"	92"	92"	92"	92"	92"	92"
	Height	87"	87"	87"	92"	92"	92"	92"
Interior	Length	10'4"	12'4"	14'4"	12'4"	14'4"	16'4"	18'4"
	Width	69"	69"	69"	69"	69"	69"	69"
	Height	67"	67"	67"	73"	73"	73"	73"
Platform Height		19"	19"	19"	20"	20"	20"	20"
Torflex EZ Lube Axles	Quantity	single	single	single	tandem	tandem	tandem	tandem
	Total Capacity	2980	2980	2980	7000	7000	7000	7000
	Type	drop	drop	drop	drop	drop	drop	drop
Brakes		opt.	opt.	opt.	4 wheel electric	4 wheel electric	4 wheel electric	4 wheel electric
Tire Size		ST205/R15 15"	ST205/R15 15"	ST205/R15 15"	ST205/R15 15"	ST205/R15 15"	ST205/R15 15"	ST205/R15 15"
Tire Load Range		C	C	C	C	C	C	C
Wheel Bolt Pattern		5 - 4 1/2	5 - 4 1/2	5 - 4 1/2	5 - 4 1/2	5 - 4 1/2	5 - 4 1/2	5 - 4 1/2
Hitch Ball Size		2"	2"	2"	2 5/16"	2 5/16"	2 5/16"	2 5/16"
Hitch Height to Top of Ball		17"	17"	17"	20"	20"	20"	20"
Hitch Weight		150	165	180	190	200	230	250
Curb Weight		1100	1340	1560	1860	1960	2260	2460
GVWR		2980	2980	2980	7000	7000	7000	7000
Payload Capacity (Avg.)		1880	1640	1420	5140	5040	4740	4540
Rear Doors	Std.	double ramp*	double ramp*	double ramp*	double ramp*	double ramp*	double ramp*	double ramp*
	Opt.							
Camlocks		yes	yes	yes	yes	yes	yes	yes
Rear Opening	Dbl Door	61 1/4"	61 1/4"	61 1/4"	61 1/4"	61 1/4"	61 1/4"	61 1/4"
	Ramp Door	63"	63"	63"	63"	63"	63"	63"
	Height	60"	60"	60"	66"	66"	66"	66"
12V Female/Male Connec.		4 way	4 way	4 way	7 way	7 way	7 way	7 way
ABS Front Cap		yes	yes	yes	yes	yes	yes	yes
Prefinished Aluminum Skin		.030	.030	.030	.030	.030	.030	.030
Interior Walls		3/8" ply	3/8" ply	3/8" ply	3/8" ply	3/8" ply	3/8" ply	3/8" ply
Floor		3/4" ply	3/4" ply	3/4" ply	3/4" ply	3/4" ply	3/4" ply	3/4" ply
Front Jack		yes	yes	yes	yes	yes	yes	yes
DOT Lighting/Dbl Bulb		yes	yes	yes	yes	yes	yes	yes
Safety Chains and Hooks		yes	yes	yes	yes	yes	yes	yes
White Spoke Wheels		yes	yes	yes	yes	yes	yes	yes
Aluminum Fenders		yes	yes	yes	yes	yes	yes	yes
Breakaway Kit		opt.	opt.	opt.	yes	yes	yes	yes
Floor Crossmembers = 24" OC			Wall Studs = 16" OC			Roof Bows = 24" OC		

* Rear Ramp Door with Spring Assist

Rev 402



Haulmark's Commitment to Quality

For over 20 years Haulmark has constructed the best-built trailers in America. We recognize and value the importance of strength, durability and quality and strive to give our customers nothing less.

Haulmark designs and construction reflect a tradition of total commitment to quality. Come see why Haulmark is "the best name behind you for the long haul."

800-348-7530 • www.haulmark.com

Indiana • Pennsylvania • Utah • Georgia • Arizona

DEALER IMPRINT



Manufacturer of Steel Frame Trailers of Quality

All of the information printed was based on the latest product information available at the time of publication. Haulmark reserves the right to make changes at any time in prices, colors, materials, equipment, specifications and models and to discontinue models without notice or obligation. Photos may show optional equipment which is not a standard item on a particular unit. Please see your dealer for complete details about standard and optional equipment.

© Copyright 1998 Haulmark Industries, Inc.