

Transport



POPULAR OPTIONS

- Red, Black or White Exterior
- 24" Stoneguard
- Wall-Mounted Rope Tiedowns
- Non-Powered Roof Vent
- Wall-Mounted Dome Light



STANDARDS

- Black, White or Red ABS Front Cap
- .024 Aluminum Exterior
- 3.6 mm Lauan Interior Walls
- 2,000 lb. top Wind Front Jack
- DOT Lighting

- Safety Chains and Hooks
- Aluminum Fenders
- No Wheel Wells
- Floor, Wall and Roof 24" on Centers

THE BEST NAME BEHIND YOU FOR THE LONG HAUL

Transport Specifications

Model		TS5X8DS2	TS5X10DS2	TS6X10DS2	TS6X12DS2	TS7X14DT2	TS7X16DT2
Overall	Length	11' 4"	13' 4"	13' 4"	15' 4"	17' 4"	19' 4"
	Width	80"	80"	92"	92"	102"	102"
	Height	78 1/2"	78 1/2"	86 1/2"	86 1/2"	99"	99"
Interior	Length	8' 2"	10' 2"	10' 2"	12' 2"	14' 2"	16' 2"
	Width	57"	57"	69"	69"	81"	81"
	Height	59"	59"	65"	65"	77"	77"
Platform Height		19"	19"	20"	20"	21"	21"
Axle	Type	spring	spring	spring	spring	spring	spring
	Quantity	single	single	single	single	tandem	tandem
	Capacity	2,500 lb.	2,500 lb.	2,990 lb.	2,990 lb.	7,000 lb.	7,000 lb.
Brakes		none	none	none	none	4 wheel, elec.,10x2 1/2	4 wheel, elec.,10x2 1/2
Hubs	Type	idler	idler	idler	idler	brake	brake
		drop	drop	drop	drop	straight	straight
Tires	Type	bias ply	bias ply	bias ply	bias ply	bias ply	bias ply
	Size	ST175/80D13 13"	ST175/80D13 13"	ST205/75D14 14"	ST205/75D14 14"	ST205/75D14 14"	ST205/75D14 14"
Wheels	Type	white spoke, steel	white spoke, steel	white spoke, steel	white spoke, steel	white spoke, steel	white spoke, steel
Ball Hitch Size		2"	2"	2"	2"	2 5/16"	2 5/16"
Ball Height to Top of Ball		17"	17"	20"	20"	21"	21"
Hitch Weight		120	140	160	180	240	260
Curb Weight		820	1,020	1,070	1,280	1,760	2,010
GVWR		2,500	2,500	2,990	2,990	7,000	7,000
Payload Capacity		1,680	1,480	1,920	1,710	5,240	4,990
Rear Doors	Type	single, swing	single, swing	double doors	double doors	double doors	double doors
	Opening Width	50"	50"	61"	61"	73"	73"
	Opening Height	54"	54"	60"	60"	72"	72"
	Lock	cam lock	cam lock	cam lock	cam lock	cam lock	cam lock
Side Door	Type	n/a	n/a	32"	32"	36"	36"
	Width	n/a	n/a	32"	32"	36"	36"
	Height	n/a	n/a	56"	56"	68"	68"
	Lock	n/a	n/a	bar lock	bar lock	bar lock	bar lock
12V Female/Male Connector		4 way	4 way	4 way	4 way	7 way	7 way
Interior Floor		5/8" plywood	5/8" plywood	5/8" plywood	5/8" plywood	3/4" plywood	3/4" plywood
Aluminum Fenders		yes	yes	yes	yes	yes	yes
ABS Front Cap		yes	yes	yes	yes	yes	yes
DOT Lighting/Dbl Bulb		yes	yes	yes	yes	yes	yes

Rev 402



Red



Black



White

Haulmark Industries, Inc.
14054 CR 4
P.O. Box 281
Bristol, IN 46507
ph (574) 825-5867
fax (574) 825-9816

Haulmark of Georgia
P.O. Box 1286
122 Glen Bass Rd.
Fitzgerald, GA 31750
ph (912) 423-2202
fax (912) 423-2330

Haulmark's Commitment to Quality

For over 20 years Haulmark has constructed the best-built trailers in America. We recognize and value the importance of strength, durability and quality and strive to give our customers nothing less.

Haulmark designs and construction reflect a tradition of total commitment to quality. Come see why Haulmark is "the best name behind you for the long haul."

800-348-7530 • www.haulmark.com

Indiana Pennsylvania Utah Georgia Arizona

DEALER IMPRINT



Manufacturer of Steel Frame Trailers of Quality

All of the information printed was based on the latest product information available at the time of publication. Haulmark reserves the right to make changes at any time in prices, colors, materials, equipment, specifications and models and to discontinue models without notice or obligation. Photos may show optional equipment which is not a standard item on a particular unit. Please see your dealer for complete details about standard and optional equipment.

© Copyright 1998 Haulmark Industries, Inc.